

## 5 REFERENCES FOR LP GAS STORAGE AND HANDLING ACTIVITIES

- Dangerous Goods Safety (Storage and Handling of Non-explosives) Regulations 2007
- Static storage – see AS 1596 *The storage and handling of LP Gas*
- Exchange LP Gas cylinder facilities – see Appendix G of AS 1596
- Mobile use of oxy-fuel systems – see AS 4839 *The safe use of portable and mobile oxy-fuel gas systems for welding, cutting, heating and allied processes*
- Decanting – LP Gas suppliers have standard procedure; also see Appendix J of AS 1596

[www.dmp.wa.gov.au/  
ResourceSafety](http://www.dmp.wa.gov.au/ResourceSafety)

ANGEROUS GOODS SAFETY ACT 2004  
DANGEROUS GOODS  
SAFETY (STORAGE AND  
HANDLING OF NON-  
EXPLOSIVES)  
REGULATIONS 2007

## 6 REFERENCES FOR LP GAS TRANSPORT ACTIVITIES

- Transport of LP Gas in quantities exceeding 250 litres is described as **placard load transport** and is regulated under the Dangerous Goods Safety (Road and Rail Transport of Non-explosives) Regulations 2007 ([www.slp.wa.gov.au](http://www.slp.wa.gov.au))
- Technical requirements for transport are contained in the *Australian Dangerous Goods Code, 7th edition* ([www.ntc.gov.au](http://www.ntc.gov.au))
- Responsibilities are defined for:
  - Consignor
  - Driver
  - Prime contractor
  - Loader
  - Vehicle owner

